



DATA SHEET 12006.750.99900

Folabase Soft A

The Folabase Soft A is the self-adhesive modulation of our modern and flexible Folabase Soft u. The two-layer compound made of dimensionally stable polyester and extremly ductile polyurethane ensures an extremely high dimensional stability and thus, stable thickness. The soft polyrethane layer absorbs mechanical forces and ensures a good resistance against paper jam. http://oneminutefilm.tv/en/yuqadeyo?campaign=folex

| Formats | | |
|-----------------|--------------------------|------------------------|
| Art.Number | Nominal thickness (inch) | Nominal thickness (mm) |
| 12006.350.99900 | .0138 | 0.35 |
| 12006.400.99900 | .0157 | 0.40 |
| 12006.450.99900 | .0177 | 0.45 |
| 12006.500.99900 | .0197 | 0.50 |
| 12006.550.99900 | .0217 | 0.55 |
| 12006.600.99900 | .024 | 0.60 |
| 12006.700.99900 | .028 | 0.70 |
| 12006.750.99900 | .0295 | 0.75 |
| 12006.800.99900 | .0315 | 0.80 |
| 12006.900.99900 | .035 | 0.90 |
| 12006.950.99900 | .037 | 0.95 |
| 12006.110.99900 | .043 | 1.10 |
| 12006.130.99900 | .051 | 1.30 |
| 12006.140.99900 | .055 | 1.40 |

Rolls Art.Number Nominal thickness Nominal thickness Roll width / Roll Length of roll (inch) usuable width (mm) 12006.550.99900 .0217 0.55 12006.350.11300 .0138 0.35 1270 50 12006.400.11300 1270 50 .0157 0.40 12006.450.11300 1270 .0177 0.45 50



| 12006.500.11300 | .0197 | 0.50 | 1270 | 50 |
|-----------------|-------|------|------|----|
| 12006.550.11300 | .0217 | 0.55 | 1270 | 50 |
| 12006.600.11300 | .024 | 0.60 | 1270 | 50 |
| 12006.700.11300 | .028 | 0.70 | 1270 | 50 |
| 12006.750.11300 | .0295 | 0.75 | 1270 | 50 |
| 12006.800.11300 | .0315 | 0.80 | 1270 | 50 |
| 12006.900.11300 | .035 | 0.90 | 1270 | 50 |
| 12006.950.11300 | .037 | 0.95 | 1270 | 50 |
| 12006.110.11300 | .043 | 1.10 | 1270 | 50 |
| 12006.130.11300 | .051 | 1.30 | 1270 | 50 |
| 12006.140.11300 | .055 | 1.40 | 1270 | 50 |

Technical data

Characteristic







- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier
- Adhesive light

Finish

Soft surface

Compatibility

- For Blanket Cylinder
- For a hard substrate packing.
- Paperlike underpacking film

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.



