

*Rely on us.*SM



HDP® Appro HMK 1

Highly effective blanket and roller wash

Roller and blanket wash for all Sheetfed presses

Product Features

- HDP® Appro HMK 1 is a water miscible formulation which is Fogra approved, certified as acceptable by Heidelberg, Manroland and KBA on their range of presses.
- HDP® Appro HMK 1 complies with health and safety guidelines for flammability and environmental considerations as well as the corrosion inhibitors demanded by the manufacturers.
- Highly effective when used as a blanket and roller wash on automatic or manual systems.
- HDP® Appro HMK 1's innovative formulation makes it much more economical than many competitors' products.
- It can be mixed at a ratio of 30% Appro HMK 1 to 70% water without any reduction in performance. As a result less product is used leading to less waste disposal, an important factor in today's increasingly ecology conscious environment.

Advantages of HDP® Appro HMK 1

- Water miscible.
- Economical.
- Excellent ink solvency.
- FOGRA approved.
- Recommended for automatic roller and blanket washing equipment.
- Safe on all plates including CtP material.
- High flashpoint (>60°C) AIII.



FlintGroup

HDP® Appro HMK 1

Features	Advantages	Benefits
<ul style="list-style-type: none">• Superior ink solvency power over similar marketed products.	<ul style="list-style-type: none">• Faster wash-ups.• Less volume required.	<ul style="list-style-type: none">• Reduced downtime.• Cost effective.
<ul style="list-style-type: none">• Economical in use.	<ul style="list-style-type: none">• Lower consumption.• Less waste solvent.	<ul style="list-style-type: none">• Cost effective.• Reduced disposal considerations.
<ul style="list-style-type: none">• Approved by leading original equipment manufacturers.	<ul style="list-style-type: none">• Compatible with automatic wash systems.• Validates warranty.	<ul style="list-style-type: none">• Versatility of application.• No rubber swell on press components.
<ul style="list-style-type: none">• High flashpoint (AIII classification).	<ul style="list-style-type: none">• Low-hazard.	<ul style="list-style-type: none">• Environmentally responsible.• Safer in use/storage considerations.
<ul style="list-style-type: none">• Low odour.	<ul style="list-style-type: none">• Safer pressroom environment.	<ul style="list-style-type: none">• Improved conditions for pressmen.

Product code	KV10-0V6G-#### (final 4 digits relate to pack size).
Pack size	10 litres (DTF9), 200 litres (DTN1) and 1000 litres (DTU0).
Application	Use as instructed in automatic systems, or mix with up to 70% water for manual applications. For additional information please refer to safety and data sheets.
Flashpoint	>60°C (AII).

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
Varn House, Brinell Drive,
Northbank Industrial Park, Irlam,
Greater Manchester, M44 5BL, UK.

T +44 (0)161 776 5412
F +44 (0)161 776 5415
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group.